

Minimum Length of Lap Splices* (Off-Centered Bars)

Bar Size	Diameter (d, in.)	2005 MSJC*** Allowable Stress Design		2005 MSJC*** Strength Design	2006 MBC Allowable Stress Design (48d, in.)**	2006 MBC*** Strength Design	
		8" CMU	12" CMU	8" CMU		8" CMU	12" CMU
#3	3/8	15.1	15.1	15.1	18	15.1	15.1
#4	4/8	25.2	25.2	25.2	24	25.2	25.2
#5	5/8	39.3	39.3	39.3	30	39.3	39.3
#6	6/8	73.6	73.6	73.6	36	73.6	73.6
#7	7/8	100.2	100.2	100.2	42	100.2	100.2
#8	8/8	151.0	151.0	151.0	48	151.0	151.0

* Bar placed off center (2" cover), Grade 60 steel, 48" o.c. spacing, and $f'_m=1500$ psi

** Not less than 12 inches and in no case shall the length of lapped splice less than 40 bar diameters. Where design tensile stresses in the reinforcement are greater than 80% of F_s , lap length shall be increased not less than 50% of the minimum required length.

*** Not less than 12 inches.

The decision to utilize this information is not within the purview of the MIM, and persons making use of this information do so at their own risk. MIM makes no representation or warranties, expressed or implied, with respect to the accuracy or suitability of this information. MIM and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, which may result from the use of this information. This information is not to be interpreted as indicating compliance with, or waiver of, any provision of any applicable building code, ordinance, standard or law.